

Postek 博思得

COMPACT & AFFORDABLE



KEY FEATURE

- Supports both Direct Thermal and Thermal Transfer printing
- 32 bit embedded ARM CPU
- Adjustable media sensor
- Standard RS-232 Serial and USB communication ports
- Large ribbon roll capacity: 360M

General Specifications

Model	C168
Printing method	Direct Thermal & Thermal Transfer
Printing resolution	203dpi (8dots/mm)
Max printing speed	3ips (76.2mm/s)
Max printing width	4.09" (104mm)
Max printing length	20" (508mm)
Memory	2MB SDRAM, 2MB Flash ROM
Media	Roll-feed, die cut, continuous, fan-fold, tags, tickets in plain paper or thermal paper; Width: 110mm max. /27mm min Supply Roll: OD 4" (102mm) max., ID 1" (25.4mm) min. Thickness: 0.003" ~ 0.012" (0.06 ~ 0.15mm), including liner if applicable
Ribbon	Wax, Wax / Resin, Resin. Ribbon roll: OD 3" (76.2mm) max., ID 1" (25.4mm) core Max width: 110mm; Max length: 360m
Fonts	Postek internal printing fonts All windows fonts
Barcode Type	1D Barcode: Code 39, Code 93, Code 128/subset A,B,C, Codabar, Interleave 2 of 5, UPC A/E 2 and 5 add-on, EAN-13/8/128, UCC-128, Postnet, Plessey, HBIC, Telepen, FIM 2D Barcode: PDF 417, QR Code, Data Matrix
Media sensor	Reflective (Adjustable)
Interfaces	RS-232 serial, USB
Power adapter	Input: AC100 ~ 240V, 47 ~ 63Hz Output: DC24V, 2.0A
Weight	2.8kgs
Dimensions (mm)	W236 x D291 x H199
Operating environment	Temperature: 40F ~ 100F (0°C - 40 °C)
Optional items	Cutter kit, peeler kit

- All specifications are subject to change without prior notice.
- All companies and/or product names are trademarks and/or registered trademarks of their respective owners.

Authorized Distributor:

Postek 博思得